

CS9603

- Horizontal rotation range 0° ~ 325°
- Vertical rotation range 0° ~ 90°
- Auto camera tour and 16 preset points
- Color 1/3" CCD sensor
- Support static or dynamic IP
- Includes 16-ch software



Warranty
1
YEAR
Warranty

Model	GS9603
Pan Range	0-325°
Tilt Range	0-90°
Auto Pan Range	0-325°
Preset Number	16
Alarm Input	2
Alarm Output	2 NC/NO contact 3A@ 125VAC / 30VDC
Camera	
Image Pick-up Device	Color 1/3" solid-state CCD sensor
Effective Picture Elements	NTSC: 542x492 (HxV), PAL: 542x582 (HxV)
Horizontal Resolution	380TV lines/480TV lines
Minimum Illumination	0.2 LUX @ F2.0
Electronic Shutter	NTSC: 1/60 - 1/100,000 sec, PAL: 1/50-1/100,000 sec
Auto Iris Control	Video-Drive Iris Control
Auto Gain Control	Built in
Auto White Balance	Color Temperature: 2500°K~ 9500°K
Gama Characteristic	0.45
SYNC System	Internal, Negative sync.
Video Output	IVp-p/75Ohms.
Lens Furnished	Board lens f 3.6 mm/F2.0
IP	
Codec	JPEG, 3 levels
Resolution	640x480,352x288,320x240,176x144
Frame Rate	Up to 30fps for all resolutions
Compatibility	Windows 2000, XP
LAN I/F	10/100M
Notification	Email, FTP , Popup message
OS	Linux
Type Of IP Address	Static or Dynamic
Local Backup	CF Memory Card
Viewer	Microsoft Internet Explorer 5.0 or later
IP Filtering	Yes
Networking Protocol	TCP/IP, HTTP, SMTP, FTP, NTP, DNS, DDNS, ARP and DHCP
Streaming Protocol	ActiveX
Communication Protocol	PPPoE
Gross Dimension	21cm x 20cm x 28cm (8.3in x 7.8in x 11in)
Gross Weight	1.6Kg (3.5lb)